

PORTABLE & RUGGED

SUBMERSIBLE ROBOTS

MADE IN CANADA ♦



*4K CAMERA SMART AUX LIGHTS



*4K CAMERA WORKER AUX LIGHTS

DTG2 *STARTER*

100M (330FT) DEPTH RATING
 50M (164FT) TETHER +
 CONTROLLER +

DTG2 *PRO*

100M (330FT) DEPTH RATING
 75M (250FT) TETHER +
 CARRYING CASE +
 CONTROLLER

DTG2 *SMART*

150M (500FT) DEPTH RATING
 DEPTH, HEADING, TEMP SENSOR +
 75M (250FT) TETHER
 CARRYING CASE
 CONTROLLER

DTG2 *WORKER*

150M (500FT) DEPTH RATING
 100M (330FT) TETHER +
 GRABBER ARM +
 DEPTH, HEADING, TEMP SENSOR
 CARRYING CASE
 CONTROLLER

THESE GUYS PRODUCTS WORK BEYOND COMPARE AND THEY WILL HELP YOU IN ANY WAY POSSIBLE WITH ANY QUESTION YOU HAVE.

DAVID H. - PITTSBURG TANK & TOWER

DTG2 OPTIONS & ADD-ONS

CAMERAS & MOUNTS



4K CAMERA



AUXILIARY CAMERA



GOPRO MOUNT


RECORDING & VIEWING SYSTEMS



DIGITAL VIDEO RECORDER



VIDEO GLASSES



UNDERWATER CONTROLLER

SONAR



SINGLE & MULTI BEAM SONAR

LIGHTING



EXTERNAL FLOOD LIGHTS



AUXILIARY LIGHTS

SAMPLING & MEASUREMENT TOOLS



SEDIMENT SAMPLER



WATER SAMPLER



LASER SCALER



NDT TOOLS



POSITIONING SYSTEM

CONTACT FOR MORE DETAILS

DTG2 FEATURES

KEY HIGHLIGHTS



150M // 500FT



HD LOW-LIGHT CAMERA



UP TO 8 HOURS



SWIFT PERFORMANCE



ONE CARRYING CASE



UNMATCHED MOBILITY



LOW MAINTENANCE

DTG2 // SPECIFICATIONS

ROV GENERAL SPECIFICATIONS :

WIDTH :	325 MM (12.8")
HEIGHT :	258 MM (10.2")
LENGTH :	279MM (11.0")
WEIGHT (IN AIR) :	8.5 KG (18.7 LB)
BODY MATERIAL :	DIE CAST ALUMINUM
WINDOW MATERIAL :	ACRYLIC
DEPTH RATING :	150 M (500 FT)
OPERATING TEMP :	-5°C TO 40°C (23°F - 104°F)
WARRANTY :	1 YEAR - PARTS AND LABOUR

ROV ELECTRICAL SYSTEM :

SYSTEM VOLTAGE :	19.2 VDC
BATTERY RUN TIME :	6 - 8 HOURS
BATTERY RECHARGE :	1.5 HOURS
THRUSTER CONTROL :	2x INDEPENDENT CONTROL INFINITELY VARIABLE 100% REVERSIBLE

LIGHTS AND CAMERA :

CAMERAS :	1/3 SONY CCD 700 HD 0.001 LUX 320° RANGE OF VIEW
	SONY ACTION CAM 4K VIDEO RECORDING
LIGHTING :	HIGH EFFICIENCY LED 300 LUMENS TRACKING WITH CAMERA 1200 LUMENS WITH OPTIONAL AUXILIARY LIGHTING

ROV TETHER :

TETHER DIAMETER :	5.0 MM (0.19")
TETHER WEIGHT :	NEUTRALLY BUOYANT IN WATER
MAXIMUM WORKING STRENGTH :	25 KG (55 LB)
MINIMUM BREAKING STRENGTH :	90 KG (200 LB)